

Q6 EDGE[®] Z shown in *Back in Black* with iLevel[®] technology

Q6 edge Z

The Q6 Edge® Z utilizes powerful 4-pole motors for maximum torque and Mid-Wheel 6® design for aggressive outdoor performance and precision indoor maneuverability. The Q6 Edge® Z accepts a broad range of exclusive seating and electronics options for unmatched adaptability and rehab capability, and is available with our iLevel® technology.

QUANTUM®

Specifications

DRIVE WHEELSStandard: 14" Pre-umatic Ditional: 14" Pre-umatic 14" KnobbyCASTER WHEELSFort: 6" Solid Rear: 6" SolidANTI-TIP WHEELSN/AANTI-TIP WHEELSN/AMAXIMUM SPEEDStandard: Up to 6 mph Optional: Up to 5 mph ¹⁰ GROUND CLEARANCE3" at frame baseGROUND CLEARANCE3" at frame baseOVERALL LENGTH235.6"SEATING SIZES56.5"SEATING SIZESWidth: 10-24"Depth: 10-24"Depth: 10-24"TRU-BALANCE® 3 STATICWidth: 12-24"TRU-BALANCE® 3 STATICWidth: 12-24"TRU-BALANCE® 3 STATICWidth: 12-24"SEAT-TO-FLOOR HEIGHTS16.5-18.5"SYNERGY®/TRU-BALANCE® 3 STATIC 516.5-18.5"STNERGY®/TRU-BALANCE® 3 STATIC 519.375-21.375"TRU-BALANCE® 3 POWER TILT 519.375-21.375"TRU-BALANCE® 3 ILEVEL® & TILT 519.375-21.375"GROMOTO PACKAGE6-0uc JLEVELAVAILABLE ELECTRONICS 86A.0FLOORT 4<			
Rear: 6" SolidANTI-TIP WHEELSN/AMAXIMUM SPEEDStandard: Up to 5 mph10GROUND CLEARANCE3" at frame bassGROUND CLEARANCE3" at frame bassTURNING RADIUS219.75"OVERALL LENGTH235.6"BASE WIDTH26.25"SEATING SIZESWidth: 10-24"POPth: 10-24"Depth: 10-24"TRU-BALANCE® 3 STATICWidth: 12-24"TRU-BALANCE® 3 POWER TILTWidth: 12-24"POPth: 12-24"Depth: 12-24"SEATTO-FLOOR HEIGHTS16.5-18.5"SYNERGS®/TRU-BALANCE® 3 STATIC516.5-18.5"TRU-BALANCE® 3 STATIC516.5-18.5"TRU-BALANCE® 3 STATIC516.5-18.5"TRU-BALANCE® 3 STATIC516.5-18.5"TRU-BALANCE® 3 STATIC516.5-18.5"TRU-BALANCE® 3 ILEVEL® & TILT519.375-21.375"TRU-BALANCE® 3 ILEVEL® & TILT515.105."BATTERY WEIGHT752 lbs. eachAVAILABLE ELECTRONICS75A Q-Logic 2 NE+ 100A Q-Logic 2 EXBATTERY CHARGER8A Off-boardMOTOR PACKAGES4-Pole Mid-Wh-LMOTOR PACKAGES4-Pole Mid-Wh-LWEIGHT CAPACIT300 lbs.	DRIVE WHEELS	Optional: 14" Pneumatic	
MAXIMUM SPEEDStandard: Up to 6 mph Optional: Up to 8 mph ¹⁰ GROUND CLEARANCE3" at frame bassTURNING RADIUS 219.75"OVERALL LENGTH 235.6"BASE WIDTH26.25"SEATING SIZESWidth: 10-24"Depth: 10-24"Depth: 10-24"TRU-BALANCE® 3 STATICWidth: 12-24"TRU-BALANCE® 3 POWER TILTWidth: 12-24"TRU-BALANCE® 3 POWER TILTWidth: 12-24"SEAT-TO-FLOOR HEIGHTS16.5-18.5"SYNERGY®/TRU-BALANCE® 3 STATIC 518.125-20.125"TRU-BALANCE® 3 POWER TILT 519.375-21.375"TRU-BALANCE® 3 ILEVEL® & TILT 519.375-21.375"Group 24BATTERY WEIGHT 7SZISSCOUP 24BATTERY WEIGHT 752 lbs. eachAVAILABLE ELECTRONICS 8375A Q-Logic 2 NE+ 100A Q-Logic 2 EXBATTERY CHARGER8A Off-boardMOTOR PACKAGES4-Pole Mid-Wiel 6®WEIGHT CAPACITY300 lbs.	CASTER WHEELS		
Optional: Up to 8 mph¹0GROUND CLEARANCE3" at frame baseTURNING RADIUS19.75"OVERALL LENGTH35.6"BASE WIDTH26.25"SEATING SIZESWidth: 10-24"Depth: 10-24"Depth: 10-24"TRU-BALANCE® 3 STATICWidth: 12-24"TRU-BALANCE® 3 STATICWidth: 12-24"TRU-BALANCE® 3 POWER TILTWidth: 12-24"Depth: 12-24"Depth: 12-24"SYNERGY®/TRU-BALANCE® 3 STATIC16.5-18.5"SYNERGY®/TRU-BALANCE® 3 STATIC16.5-18.5"TRU-BALANCE® 3 POWER TILT18.125-20.125"SYNERGY®/TRU-BALANCE® 3 STATIC18.125-20.125"TRU-BALANCE® 3 POWER TILT19.375-21.375"TRU-BALANCE® 3 ILEVEL® & TILT19.375-21.375"TRU-BALANCE® 3 ILEVEL® & TILT19.375-21.375"ANAILABLE ELECTRONICSGroup 24AVAILABLE ELECTRONICS25 lbs. eachAVAILABLE ELECTRONICS75 A Q-Logic 2 NE+ 100A Q-Logic 2 EXBATTERY CHARGER8A Off-boardMOTOR PACKAGES4-Pole Mid-Where 6®WEIGHT CAPACIT300 lbs.	ANTI-TIP WHEELS	N/A	
TURNING RADIUS 219.75"OVERALL LENGTH 235.6"BASE WIDTH 26.25"26.25"SEATING SIZESWidth: 10-24"Depth: 10-24"TRU-BALANCE® 3 STATIC 1Width: 12-24"Depth: 12-24"TRU-BALANCE® 3 POWER TILT 2Width: 12-24"Depth: 12-24"TRU-BALANCE® 3 POWER TILT 2Width: 12-24"Depth: 12-24"SEAT-TO-FLOOR HEIGHTSWidth: 12-24"Depth: 12-24"SYNERGY®/TRU-BALANCE® 3 STATIC 516.5-18.5"STATIC 18.125-20.125"TRU-BALANCE® 3 POWER TILT 518.125-20.125"STATIC 19.375-21.375"TRU-BALANCE® 3 ILEVEL® & TILT 519.375-21.375"STATIC 19.375-21.375"TRU-BALANCE® 3 ILEVEL® & TILT 519.375-21.375"STATIC 19.375-21.375"MANUAL RECLINE 1YesSTATIC 19.375BATTERY SIZE 3Group 24STATIC 19.375BATTERY WEIGHT 752 lbs. eachSTATIC 19.375AVAILABLE ELECTRONICS 8375 A Q-Logic 2 NE+100A Q-Logic 2 EXBATTERY CHARGER 1SA Off-boardMOTOR PACKAGES 34-Pole Mid-Whe 16®WEIGHT CAPACITY 300 lbs.300 lbs.	MAXIMUM SPEED ¹		
OVERALL LENGTH 235.6"BASE WIDTH26.25"SEATING SIZESSYNERGY®Width: 10-24"SEATING SIZESWidth: 12-24"Depth: 10-24"TRU-BALANCE® 3 STATICWidth: 12-24"Depth: 12-24"TRU-BALANCE® 3 POWER TILTWidth: 12-24"Depth: 12-24"SEAT-TO-FLOOR HEIGHTSWidth: 12-24"Depth: 12-24"SYNERGY®/TRU-BALANCE® 3 STATIC 516.5-18.5"Setter 12-24"TRU-BALANCE® 3 POWER TILT 518.125-20.125"Setter 12-24"TRU-BALANCE® 3 IEVEL® & TILT 519.375-21.375"Setter 12-24"MANUAL RECLINE 7YesSetter 12-24"BATTERY SIZE 3Group 24Setter 12-24"AVAILABLE ELECTRONICS 875A Q-Logic 2 N=+BATTERY CHARGER8A Off-boardMOTOR PACKAGES4-Pole Mid-Wh= 6®WEIGHT CAPACITI300 lbs.	GROUND CLEARANCE	3" at frame base	
BASE WIDTH26.25"SEATING SIZESWidth: 10-24"Depth: 10-24"TRU-BALANCE® 3 STATICWidth: 12-24"Depth: 12-24"TRU-BALANCE® 3 POWER TILTWidth: 12-24"Depth: 14-24"TRU-BALANCE® 3 POWER TILTWidth: 12-24"Depth: 12-24"SEAT-TO-FLOOR HEIGHTSWidth: 12-24"Depth: 12-24"SYNERGY®/TRU-BALANCE® 3 STATIC 516.5-18.5"Depth: 12-24"TRU-BALANCE® 3 STATIC 516.5-18.5"Image: Complexity of the state	TURNING RADIUS ²	19.75"	
SEATING SIZESSYNERGY®Width: 10-24"Depth: 10-24"TRU-BALANCE® 3 STATICWidth: 12-24"Depth: 12-24"TRU-BALANCE® 3 POWER TILTWidth: 12-24"Depth: 14-24"TRU-BALANCE® 3 LIFTWidth: 12-24"Depth: 12-24"SEAT-TO-FLOOR HEIGHTSWidth: 12-24"Depth: 12-24"SYNERGY®/TRU-BALANCE® 3 STATIC 516.5-18.5"Section 1000000000000000000000000000000000000	OVERALL LENGTH ²	35.6"	
SYNERGY®Width: 10-24"Depth: 10-24"TRU-BALANCE® 3 STATICWidth: 12-24"Depth: 12-24"TRU-BALANCE® 3 POWER TILTWidth: 12-24"Depth: 12-24"SEAT-TO-FLOOR HEIGHTSWidth: 12-24"Depth: 12-24"SYNERGY®/TRU-BALANCE® 3 STATIC16.5-18.5"SectionTRU-BALANCE® 3 STATIC18.125-20.125"SectionTRU-BALANCE® 3 POWER TILT19.375-21.375"SectionTRU-BALANCE® 3 ILEVEL® & TILT19.375-21.375"SectionMANUAL RECLINEYesSectionSectionBATTERY WEIGHT52 lbs. eachSectionSectionAVAILABLE ELECTRONICSSA Off-DoardSectionSectionBATTERY CHARGE8A Off-boardSectionSectionMOTOR PACKAGES4-Pole Mid-Wh=6®SectionSectionWEIGHT CAPACITY300 lbs.SectionSection	BASE WIDTH	26.25"	
TRU-BALANCE® 3 STATICWidth: 12-24"Depth: 12-24"TRU-BALANCE® 3 POWER TILTWidth: 12-24"Depth: 14-24"TRU-BALANCE® 3 LIFTWidth: 12-24"Depth: 12-24"SEAT-TO-FLOOR HEIGHTSWidth: 12-24"Depth: 12-24"SYNERGY®/TRU-BALANCE® 3 STATIC 516.5-18.5"STRU-BALANCE® 3 POWER TILT 518.125-20.125"STRU-BALANCE® 3 ILEVEL® & TILT 519.375-21.375"STRU-BALANCE® 3 ILEVEL® & TILT 519.375-21.375"SBATTERY SIZE 3Group 24SSBATTERY WEIGHT 752 lbs. eachSAVAILABLE ELECTRONICS 875A Q-Logic 2 NE+ 100A Q-Logic 2 EXSBATTERY CHARGER8A Off-boardSMOTOR PACKAGES4-Pole Mid-Wh= 6®SWEIGHT CAPACITY300 lbs.S	SEATING SIZES		
TRU-BALANCE® 3 POWER TILTWidth: 12-24"Depth: 14-24"TRU-BALANCE® 3 LIFTWidth: 12-24"Depth: 12-24"SEAT-TO-FLOOR HEIGHTSStattic 516.5-18.5"SYNERGY®/TRU-BALANCE® 3 STATIC 518.125-20.125"TRU-BALANCE® 3 ILEVEL® & TILT 519.375-21.375"TRU-BALANCE® 3 ILEVEL® & TILT 519.375-21.375"MANUAL RECLINEYesBATTERY SIZE 3Group 24Group 24Statter 5AVAILABLE ELECTRONICS 875A Q-Logic 2 NE+ 100A Q-Logic 2 EXBATTERY CHARGER8A Off-boardMOTOR PACKAGES4-Pole Mid-Wheel 6®WEIGHT CAPACITY300 lbs.	SYNERGY®	Width: 10-24" Depth: 10	-24"
TRU-BALANCE® 3 LIFWidth: 12-24"Depth: 12-24"SEAT-TO-FLOOR HEIGHTS16.5-18.5"SYNERGY®/TRU-BALANCE® 3 STATIC 516.5-18.5"TRU-BALANCE® 3 POWER TILT 518.125-20.125"TRU-BALANCE® 3 ILEVEL® & TILT 519.375-21.375"MANUAL RECLINEYesBATTERY SIZE 3Group 24BATTERY WEIGHT 752 lbs. eachAVAILABLE ELECTRONICS 875A Q-Logic 2 NE+ 100A Q-Logic 2 EXBATTERY CHARGER8A Off-boardMOTOR PACKAGES4-Pole Mid-Wheel 6®WEIGHT CAPACITY300 lbs.	TRU-BALANCE® 3 STATIC	Width: 12-24" Depth: 12	-24"
SEAT-TO-FLOOR HEIGHTSSYNERGY®/TRU-BALANCE® 3 STATIC 516.5-18.5"TRU-BALANCE® 3 POWER TILT 518.125-20.125"TRU-BALANCE® 3 ILEVEL® & TILT 519.375-21.375"MANUAL RECLINEYesBATTERY SIZE 3Group 24BATTERY WEIGHT 752 lbs. eachAVAILABLE ELECTRONICS 875A Q-Logic 2 NE+ 100A Q-Logic 2 EXBATTERY CHARGER8A Off-boardMOTOR PACKAGES4-Pole Mid-Wheel 6®WEIGHT CAPACITY300 lbs.	TRU-BALANCE® 3 POWER TILT	Width: 12-24" Depth: 14	-24"
SYNERGY®/TRU-BALANCE® 3 STATIC 516.5-18.5"TRU-BALANCE® 3 POWER TILT 518.125-20.125"TRU-BALANCE® 3 iLEVEL® & TILT 519.375-21.375"MANUAL RECLINEYesBATTERY SIZE 3Group 24BATTERY WEIGHT 752 lbs. eachAVAILABLE ELECTRONICS 875A Q-Logic 2 NE+ 100A Q-Logic 2 EXBATTERY CHARGER8A Off-boardMOTOR PACKAGES4-Pole Mid-Wheel 6®WEIGHT CAPACITY300 lbs.	TRU-BALANCE [®] 3 LIFT	Width: 12-24" Depth: 12	-24"
TRU-BALANCE® 3 POWER TILT 518.125-20.125"TRU-BALANCE® 3 iLEVEL® & TILT 519.375-21.375"MANUAL RECLINEYesBATTERY SIZE 3Group 24BATTERY WEIGHT 752 lbs. eachAVAILABLE ELECTRONICS 875A Q-Logic 2 NE+ 100A Q-Logic 2 EXBATTERY CHARGER8A Off-boardMOTOR PACKAGES4-Pole Mid-Wheel 6®WEIGHT CAPACITY300 lbs.	SEAT-TO-FLOOR HEIGHTS		
TRU-BALANCE® 3 iLEVEL® & TILT 519.375-21.375"MANUAL RECLINEYesBATTERY SIZE 3Group 24BATTERY WEIGHT 752 lbs. eachAVAILABLE ELECTRONICS 875A Q-Logic 2 NE+ 100A Q-Logic 2 EXBATTERY CHARGER8A Off-boardMOTOR PACKAGES4-Pole Mid-Wheel 6®WEIGHT CAPACITY300 lbs.	SYNERGY®/TRU-BALANCE® 3 STATIC ⁵	16.5-18.5"	
MANUAL RECLINE Yes BATTERY SIZE 3 Group 24 BATTERY WEIGHT 7 52 lbs. each AVAILABLE ELECTRONICS 8 75A Q-Logic 2 NE+ 100A Q-Logic 2 EX BATTERY CHARGER 8A Off-board MOTOR PACKAGES 4-Pole Mid-Wheel 6® WEIGHT CAPACITY 300 lbs.	TRU-BALANCE® 3 POWER TILT ⁵	18.125-20.125"	
BATTERY SIZE 3 Group 24 BATTERY WEIGHT 7 52 lbs. each AVAILABLE ELECTRONICS 8 75A Q-Logic 2 NE+ 100A Q-Logic 2 EX BATTERY CHARGER 8A Off-board MOTOR PACKAGES 4-Pole Mid-Wheel 6® WEIGHT CAPACITY 300 lbs.	TRU-BALANCE® 3 iLEVEL® & TILT 5	19.375-21.375"	
BATTERY WEIGHT 52 lbs. each AVAILABLE ELECTRONICS 75A Q-Logic 2 NE+ 100A Q-Logic 2 EX BATTERY CHARGER 8A Off-board MOTOR PACKAGES 4-Pole Mid-Wheel 6® WEIGHT CAPACITY 300 lbs.	MANUAL RECLINE	Yes	
AVAILABLE ELECTRONICS 75A Q-Logic 2 NE+ 100A Q-Logic 2 EX BATTERY CHARGER 8A Off-board MOTOR PACKAGES 4-Pole Mid-Wheel 6 [®] WEIGHT CAPACITY 300 lbs.	BATTERY SIZE ³	Group 24	
100A Q-Logic 2 EX BATTERY CHARGER 8A Off-board MOTOR PACKAGES 4-Pole Mid-Wheel 6® WEIGHT CAPACITY 300 lbs.	BATTERY WEIGHT 7	52 lbs. each	
MOTOR PACKAGES 4-Pole Mid-Wheel 6 [®] WEIGHT CAPACITY 300 lbs.	AVAILABLE ELECTRONICS 8		
WEIGHT CAPACITY 300 lbs.	BATTERY CHARGER	8A Off-board	
	MOTOR PACKAGES	4-Pole Mid-Wheel 6®	
BASE WEIGHT 143.5 lbs.	WEIGHT CAPACITY	300 lbs.	
	BASE WEIGHT	143.5 lbs.	

1) Speed varies with user weight, terrain type, battery charge, battery condition and tire pressure.

- 2) Without front riggings
- 3) Battery capacity may change when adding power positioning systems.
- Part of Community Use Package with 6 mph motors. Increases width by 1.5".
 All measurements +/- 1/8" with 18" x 18" seat, fixed towers, 300 lbs. weight capacity and solid tires (add 3/8" with pneumatic tires). Depths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system unless specified.
- 6) Seat backs for units without TRU-Balance® 3 seating are only available in Back in Black.
- 7) Battery weight may vary +/- 3 lbs. based on manufacturer.
- 8) All Quantum Rehab® units can be ordered with specialty controls.
- 9) Call for availability
- iLevel[®] option not available if 8 mph motors are selected.



Features

- Mid-Wheel 6[®] allows six wheels on the ground for maximum stability
- Compatible with TRU-Balance[®] 3 Power Positioning Systems
- Low impact OMNI-Casters (nylon, spherical-shaped casters) on front and rear prevent wheel hang-ups
- ATX Suspension (Active-Trac[®] with extra stability) incorporates front OMNI-Casters and semi-independent rear caster beam for enhanced performance over more varied terrain
- iLevel[®] option, featuring patented Extra Stability Technology[™], enables up to 12" of seat elevation while at walking speed (up to 3.5 mph)
- Standard switch-operated LED fender lights

Options

- iLevel[®] power adjustable seat height
- TRU-Balance[®] 3 Seating
- Q-Logic 2 Drive Controls
- 8 mph motor package
- Accu-Trac Advanced Tracking Technology⁹
- Trilogy vent tray⁹
- Compact vent tray⁹

Available on Q-Logic 2 controllers and units

with TRU-Balance® 3 (base and back)⁶

 4" wide flat-free or pneumatic knobby extended traction tires^{9,4}

Colors





Grey Back Street in Black

Military Green

ilitary



MMS Medical, Unit 81, Western Parkway Business Park, Lower Ballymount Road, Dublin 12. Tel : 01 4500582 070218 Email : sales@mmsmedical.ie www.mmsmedical.ie

MMS Medical, 51 East Gate Drive, Little Island, Cork

Tel: 021 4618000